



BRAKE FLUID SUPER DOT 5.1

Synthetic High-performance Brake Fluid

Description:

BRAKE FLUID SUPER DOT 5.1 is a high performance brake fluid especially developed for the requirements of modern passenger car brake-systems with disc or drum brakes.

Properties

- Boiling point > 270°C
- Clearly wet boiling point > 185 °C
- Viscosity index at -40°C max. 900 cSt
- Raised corrosion protection at high temperatures

Suitable for/ we recommend this product for

Brake Fluid	DOT 5.1	
Exceeds	DOT 3, DOT 4	
SAE	J 1704	
FMVSS	116	
ISO	4925 Class 5-1	

Effects

- Substantial higher operational safety even after long duration of operation
- No delay in moving the brake at temperatures up to -40°C
- Improved brake conveniences and increased safety level

Utilization

- car brake system according to DOT 4 / DOT 5
- Especially recommended for vehicles with ABS braking

Special Notes:

- Please store brake fluid only closed originally. Close tank of brake fluid airtightly straight after usage. Please unconditionally observe manufacturers information when refilling brake fluid.
- When refilling the hydraulic brake system absolute cleanliness is necessary.
- This fluid can cause damages at the paintwork.

Disposal:

Brake fluid must be gathered and disposed separately. It may not be mixed with used oil.

BRAKE FLUID SUPER DOT 5.1 is well-tolerated to comparable brake fluids. However, to guarantee complete efficiency it is recommended to use only BRAKE FLUID SUPER DOT 5.1 when refilling.

BRAKE FLUID SUPE	CR DOT 5.1	
A <mark>rt</mark> icle No.	Packaging unit	
3 <mark>2</mark> 1100	Can	250 ml
<mark>3</mark> 21101	Can	500 ml
321102	Can	1 L
321104	Can	5 L
321107	Can (tin)	5 L
321105	Pail	20 L
321106	Drum	60 L
321108	Drum	200 L

Data are subject to change. Attention: Service instructions should be observed!