

TULSA XM 4T

Premium-Fully Synthetic-Motorcycles-Motor Oil 20W-50

Description:

TULSA XM 4T is a high performance special engine oil for motorcycles with air- or water-cooled 4-stroke engines. The high additive content guarantees optimum lubrication under extreme operating conditions.

The ideal partner for sporty high- tech motorcycles in touring operations on all roads as well as off road.

Properties

- High oxidation stability
- Excellent high temperature characteristics
- High safety potential, also at boundary lubrication conditions
- Maximun shear stability

Suitable for/ we recommend this product for

SAE	20W-50			
API	SN Plus			
ACEA	A3			
We recommend this product for:				
JASO	MA2			
	· · · · · · · · · · · · · · · · · · ·			

Effects

- · High operating reliability
- Prevents black sludge formation
- Low oil consumption
- High wear stability
- No clutch picking, secure function of wet clutches.

Utilization

• Large volume 4-stroke motorbike engines

Disposal:

• TULSA XM 4T is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

• TULSA XM 4T is fully compatible to comparable lubricants and can be mixed safely. However, it is recommended to refill TULSA XM 4T only.

TULSA XM 4T			
Article No.	Packaging unit		
1205 502	Can	1 L	
1205 504	Can	5 L	
1205 505	Can	20 L	
1205 506	Drum	60 L	
1205 508	Drum	200 L	

Typical characteristics:					
Specific weight at 15°C	kg/m³	879			
Dynamic viscosity at -15°C	mPa.s	6980			
Viscosity at 40°C	mm^2/s	148			
Viscosity at 100°C	mm^2/s	18,8			
Viscosity index		144			
Flash point COC	°C	228			
Pourpoint	°C	-27			
Sulphate ashes	%	-			
TBN	mgKOH/g	10,5			

Data are subject to change. Attention: Service instructions should be observed!