

# AIROI PAO (PAO 68)

Synthetic ammonia air conditioning liquid

## Description:

AIROI PAO (PAO 68) is a synthetic air conditioning liquid on the basis of PAO.

AIROI PAO (PAO 68) is ideal for the lubrication of compressors in ammonia cooling systems.

## Properties

- Fully compatible with ammonia
- Contains a minimum of additives
- Prevents sedimentation in low temperature systems
- Reduces sedimentations in the exhaust valve
- Excellent lubricity
- No wax content
- Low vaporization
- Very low steam pressure either steam tension
- Non-hygroscopic

## Effects

- Increases the efficiency of air conditionings
- Highest operating reliability

## Suitable for/ we recommend this product for

ISO-GRADE 68 AA1

## Utilization

- Reciprocating compressors and screw compressors that are used in ammonia systems
- Gas compressors and vacuum pump-systems, where ammonia fumes develop
- Geeignet für den Einsatz mit folgenden Gasen: R717, R290, R22, R134a, R1234yf

## Miscibility:

- AIROI PAO (PAO 68) is fully mixable with customary mineral oils. However, it is recommendable to use AIROI PAO (PAO 68) only.

## AIROI PAO (PAO 68)

Article No.	Packaging unit	
1220 141	Can	500 ml
1220 142	Can	1 L

## Typical characteristics:

Specific weight at 20°C	kg/m <sup>3</sup>	833
Viscosity at 40°C	cSt	63,9
Viscosity at 100°C	cSt	-
Viscosity index		139
Flash point COC	°C	-
Pourpoint	°C	<-45
ISO-grade		68

Data are subject to change.

Attention: Service instructions should be observed!

DV/KLIMA/-  
04/2023