

LAREDO DOT 4

High-performance Brake Fluid

Description:

LAREDO DOT 4 is a high performance brake fluid developed for the requirements of modern passenger car brake-systems with disc or drum brakes.

Properties

- Wet boiling point > 160°C
- Boiling point > 260°C

Suitable for/ we recommend this product for

| Brake fluid | DOT 4 |
|-------------|---------------------------|
| Exceeds | DOT3 |
| | (US Federal Standard 116) |
| FMVSS | 116 |
| SAE | J 1704 |
| ISO | 4925 Class 4 |

Effects

- More safety by reduced boiling point drop
- For all hydraulic brake systems
- Miscible with brake fluids of equal specification

Utilization

car brake system according to DOT 3/DOT 4

Special Notes:

- Please store brake fluid only closed originally. Close tank of brake fluid airtightly straight after usage.
- Please unconditionally observe manufacturers information when refilling brake fluid.
- When refilling the hydraulic brake system absolute cleanliness is necessary.
- This fluid can cause damages at the paintwork.

Disposal

Brake fluid must be gathered and disposed separately. It may not be mixed with used oil.

Miscibility:

• **LAREDO DOT 4** is well-tolerated to comparable brake fluids. However, to guarantee complete efficiency it is recommended to use only **LAREDO DOT 4** when refilling.

| LAREDO DOT 4 | | |
|--------------|----------------|--------|
| | | |
| Article No. | Packaging unit | |
| 1221 000 | Can | 250 ml |
| 1221 001 | Can | 500 ml |
| 1221 002 | Can | 1 L |
| 1221 004 | Can | 5 L |
| 1221 007 | Can (tin) | 5 L |
| 1221 005 | Can | 20 L |
| 1221 006 | Drum | 60 L |
| 1221 008 | Drum | 200 L |