

TULSA XS 4T

Hightec-Lightrun-HC-Synthetic-Motorcycles-Motor Oil 10W40

Description:

TULSA XS 4T is a high-tech, lightrun HC synthetic engine oil of top class for 4-stroke motorcycle. Especially for modern high-revving 4-stroke motorcycle engines. Air and water cooled.

It ensures a reliable lubrication in every situation. Eases starting and switching, saves fuel and reduces oil consumption. The ideal partner for sporty high-tech motorcycles in Touring mode. Secure Function wet clutches, even under extreme operating conditions and in continuous operation.

Properties

- High wear protection
- Exceptional ageing and oxidation stability
- Extrem high temperature stability
- Very high lubrication stability
- Greatest possible engine cleanliness
- Low volatilization tendency

Effects

- Optimal operating reliability
- Excellent cold starting properties - rapid supply of all points of lubrication
- Prevents black sludge formation
- Fuel efficiency by lightrun properties
- All-year operation
- Also for wet clutches
- Reliable for racing

Suitable for/ we recommend this product for

| | |
|--------------------------------|---------|
| SAE | 10W-40 |
| API | SN Plus |
| ACEA | A3 |
| We recommend this product for: | |
| APRILIA | |
| BMW | |
| DUCATI | |
| HONDA | |
| JASO | MA2 |
| KAWASAKI | |
| MOTO-GUZZI | |
| SUZUKI | |
| TRIUMPH | |
| YAMAHA | |

Utilization

- Modern 4-stroke motorbikes

Disposal:

- **TULSA XS 4T** is assigned to category 2 of used oils and thus is free for disposal.

Miscibility:

- **TULSA XS 4T** is fully compatible to comparable lubricants and can be mixed safely. However, it is recommended to refill **TULSA XS 4T** only.

TULSA XS 4T

| Article No. | Packaging unit | |
|-------------|----------------|-------|
| 1205 742 | Can | 1 L |
| 1205 744 | Can | 5 L |
| 1205 745 | Can | 20 L |
| 1205 746 | Drum | 60 L |
| 1205 748 | Drum | 200 L |

Typical characteristics:

| | | |
|----------------------------|--------------------|------|
| Specific weight at 15°C | kg/m ³ | 863 |
| Dynamic viscosity at -25°C | mPa.s | 5590 |
| Viscosity at 40°C | mm ² /s | 97,5 |
| Viscosity at 100°C | mm ² /s | 15,1 |
| Viscosity index | | 161 |
| Flash point COC | °C | 232 |
| Pourpoint | °C | -39 |
| Sulphate ashes | % | - |
| TBN | mgKOH/g | 10,5 |

Data are subject to change.

Attention: Service instructions should be observed!

DV/MO/4T/-
07/2021